

HAULER® 1200

LOADED WITH RELENTLESS FUNCTIONALITY.

The new Hauler® 1200 is equipped to tackle the burden of every job, with a rugged truck-like design perfected by Superintendents. A large bed packed full of essential functionality can easily be converted for any task. Featuring tie down locations, divider slots and a full line of affordable accessories, transporting everything from sod to small equipment has never been easier. Your work is unforgiving, let the Hauler 1200 carry the load.

LET'S WORK.®

13.5HP KAWASAKI

GAS

1500LB TOW CAPACITY

12 CU FT CARGO BED 1200LB LOAD CAPACITY





FRAME

BODY & FINISH

STANDARD COLOR

OVERALL LENGTH

OVERALL WIDTH

WHEEL BASE

PARKING BRAKE

FRONT/REAR TIRES

OVERALL HEIGHT W/CANOPY

CUSHMAN HAULER® 1200

Welded Steel with E-Shield™ e-coat plus DuraShield™ Powder Coat

Injection Molded TPO, Painted

Forest Green

119 in (302 cm)

49.4 in (125 cm)

76.8 in (195 cm)

71 in (179 cm)









OPTIONS & ACCESSORIES

- · Limited Slip Differential
- · Locking Glove Box
- Glove Box Mat
- · Floor Mount Attachment
- Windshield
- Canopy • Power Dump
- Long Handled Tool Holders
- · Radio Holder
- · Interior Tool Hook
- LED Headlights Hi/Low
- Taillights
- Brakelights
- Hubcaps Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- Fuel Gauge

- · Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- · Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- · Weather Enclosure
- Cab
- Ball Cage • ROPS

FRONT WHEEL TRACK	35 in (89 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE	3.5 in (9 cm)
CARGO BOX CAPACITY	12 cu ft (0.34m^3)
POWER	
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal Start
AIR CLEANER	Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	980 lb (445 kg)
BED LOAD CAPACITY	800 lb (364 kg)
VEHICLE LOAD CAPACITY	1200 lb (545 kg)
SPEED	14.5 mph ± 0.5 mph (23.34 kph ± 0.8 kph)
TOWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (7.01 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum

Self-compensating, Single Point Engagement

18 x 8.5-8